



PROFESSIONAL  
LOUDSPEAKERS

# EURO PRICE LIST

## 01.01.2010

MODEL	Ohm	DESCRIPTION	PRICE (€)	ORDER CODE
<b>NEODYMIUM CONE TRANSDUCERS</b>				
<b>21" Neo</b>				
21NLW9600	4/8	21" Extended LF Neodymium Driver - 1800W AES - 97dB@1W/1mt - ISV - TSS - SDR	850,00	022218N000
21NLW9000	4/8	21" Extended LF Neodymium Driver - 1800W AES - 96dB@1W/1mt - ISV - TSS - SDR	750,00	022218N100
<b>18" Neo</b>				
18NLW9600	4/8	18" Extended LF Neodymium Driver - 1800W AES - 96,5dB@1W/1mt - ISV - TSS - SDR	580,00	022188N000
18ND9300	8	18" Extended LF Neodymium Driver - 1000W AES - 98dB@1W/1mt - ISV - DSS - DDR	420,00	022188N100
<b>15" Neo</b>				
15NLW9500	4/8	15" Extended LF Neodymium Driver - 1000W AES - 96dB@1W/1mt - ISV - DSS - DDR	335,00	022158N140
15NLW9400	8	15" Extended LF Neodymium Driver - 1000W AES - 97dB@1W/1mt - ISV - DSS - DDR	335,00	022158N180
15NLW9300	8	15" Extended LF Neodymium Driver - 1000W AES - 97dB@1W/1mt - ISV - DSS - DDR	335,00	022158N160
15ND930	4/8/16	15" Extended LF Neodymium Driver - 500W AES - 98dB@1W/1mt - DDR	258,00	022158N220
15ND830	8	15" LF Neodymium Driver - 450W AES - 98dB@1W/1mt - ISV	230,00	022158N210
15NW530	8	15" LF Neodymium Driver - 500W AES - 95,5dB@1W/1mt - ISV	230,00	022158N530
15NMB420	8	15" MB Neodymium Driver - 450W AES - 99dB@1W/1mt - ISV - SDR	200,00	022158N240
<b>12" Neo</b>				
12NLW9300	8	12" Extended LF Neodymium Driver - 1000W AES - 98dB@1W/1mt - ISV - DSS - DDR	295,00	022128N110
12ND930	8	12" LF Neodymium Driver - 500W AES - 98dB@1W/1mt - ISV - SDR	230,00	022128N220
12ND830	4/8	12" LF Neodymium Driver - 450W AES - 99dB@1W/1mt - ISV	214,00	022128N210
12NW530	8	12" Extended LF Neodymium Driver - 500W AES - 96dB@1W/1mt - ISV - DSS - SDR	220,00	022128N530
12ND710	8/16	12" Very High Output MB Neodymium Driver - 450W AES - 100,5dB@1W/1mt - DDR - ISV	240,00	022128N710
12ND610	8/16	12" Very High Output MB Neodymium Driver - 450W AES - 102dB@1W/1mt - ISV	260,00	022128N610
12NDA520	8	12" High Output MidBass Neodymium Driver - 300W AES - 100,5dB@1W/1mt - ISV - AIC	252,00	022128N300
12NMB420	8	12" MB Neodymium Driver - 300W AES - 100,5dB@1W/1mt - ISV - SDR	175,00	022128N310
<b>10" Neo</b>				
10NDA610	8	10" High Output Midrange Neodymium Driver - 400W AES - 103dB@1W/1mt - ISV - AIC	320,00	022108N210
10NMB420	8	10" High Output MidBass Neodymium Driver - 300W AES - 99,5dB@1W/1mt - ISV - AIC	232,00	022108N520
10NMB420	8/16	10" High Output MidBass Neodymium Driver - 350W AES - 99dB@1W/1mt - ISV - SDR	162,00	022108N400
<b>8" Neo</b>				
8NMB420	4/8/16	8" MB Neodymium Driver - 250W AES - 92,5dB@1W/1mt - ISV - SDR	138,00	022088N400
<b>6" Neo</b>				
6ND430	4/8/16	6" LF Neodymium Driver - 200W AES - 92,5dB@1W/1mt	112,00	022068N430
6NMB420	8/16	6" MB Neodymium Midbass - 200W AES - 100dB@1W/1mt - SDR	120,00	022068N440
6ND410	4/8/16	6" LF Neodymium Midrange - 180W AES - 102dB@1W/1mt	113,00	022068N510
<b>FERRITE CONE TRANSDUCERS</b>				
<b>21"</b>				
21LW1400	8	21" Extended LF Driver - 1500W AES - 99dB@1W/1mt - ISV - DSS - DDR	480,00	0222183110
<b>18"</b>				
18LW2400	8	18" Extended LF Driver - 1200W AES - 98dB@1W/1mt - ISV - TSS - DDR	348,00	0221882400
18LW1400	4/8	18" Extended LF Driver - 1000W AES - 98dB@1W/1mt - ISV - DSS - DDR	338,00	0221883110
18LW1250	8	18" Extended LF Driver - 1000W AES - 98dB@1W/1mt - ISV - DSS	305,00	0221883150
18W1000	8	18" Extended LF Driver - 1000W AES - 99,5dB@1W/1mt - ISV - DSS	280,00	0221884150
<b>15"</b>				
15LW1401	4/8	15" Extended LF Driver - 1000W AES - 98dB@1W/1mt - ISV - DSS - DDR	295,00	0221583120
15LW1500	8	15" Extended LF Driver - 1000W AES - 96dB@1W/1mt - ISV - DSS	295,00	0221583140
15W700	4/8	15" LF Driver - 450W AES - 99dB@1W/1mt - ISV	192,00	0221584210
15W500	8	15" LF Driver - 350W AES - 100,5dB@1W/1mt - ISV	138,00	0221584310
15MB1000	8	15" Mid Bass Driver - 850W AES - 98dB@1W/1mt - ISV	285,00	0221585100
15MB700	8	15" Very High Output MB Driver - 400W AES - 103dB@1W/1mt - ISV	204,00	0221585220
15MB606	8	15" Very High Output MB Driver - 400W AES - 101dB@1W/1mt - ISV	160,00	0221585230

MODEL	Ohm	DESCRIPTION	PRICE (€)	ORDER CODE
<b>12"</b>				
12LW1400	8	12" Extended LF Driver - 900W AES - 95dB@1W/1mt - ISV - DSS - DDR	254,00	0221283110
12W700	8	12" LF Driver - 450W AES - 98dB@1W/1mt - ISV	190,00	0221284210
12W500	4/8	12" LF Driver - 350W AES - 99,5dB@1W/1mt - ISV	132,00	0221284310
12MB1000	8	12" High Output MB Driver - 600W AES - 102dB@1W/1mt	232,00	0221285110
12MB700	8/16	12" Very High Output MB Driver - 450W AES - 101,5dB@1W/1mt - ISV - DDR	198,00	0221285220
12MB600	4/8	12" Very High Output MB Driver - 450W AES - 101dB@1W/1mt - ISV	178,00	0221285210
<b>10"</b>				
10MB600	8	10" High Output MB Driver - 450W AES - 98dB@1W/1mt - ISV	164,00	0221085210
10M600	8	10" Very High Output MB Driver - 400W AES - 102dB@1W/1mt	162,00	0221087210
10W400	8	10" LF Driver - 280W AES - 98dB@1W/1mt - ISV	130,00	0221084410
<b>8"</b>				
8MB400	4/8/16	8" MB Driver - 280W AES - 95dB@1W/1mt - ISV	105,00	0220885410
8M400	8	8" High Output MB Driver - 250W AES - 100,5dB@1W/1mt	107,00	0220887410
<b>Coax</b>				
15CX1000	8	15"/1,4" High Output Coaxial Driver - 850W / 80W (AES - 98 / 107,5 dB@1W/1mt - ISV	625,00	022158CX10
12CX800	8	12"/1,4" High Output Coaxial Driver - 600W / 80W (AES - 98 / 107,5 dB@1W/1mt - ISV	495,00	022128CX00
8CX400F	8	8"/1" High Output Coaxial Driver - 280W / 25W AES - 95 / 106 dB@1W/1mt - ISV	186,00	022088CX10
<b>NEODYMIUM COMPRESSION DRIVERS</b>				
<b>2" Neo CD</b>				
ND2080	8/16	2" exit HF Neo Driver - 160W program power - 110dB@1W/1mt - Titanium diaphragm	430,00	042108N280
ND2060	8/16	2" exit HF Neo Driver - 160W program power - 109dB@1W/1mt - Titanium diaphragm	340,00	042108N260
ND2060A	8/16	2" exit HF Neo Driver - 150W program power - 110dB@1W/1mt - Aluminum dome	330,00	0423A8M600
<b>1.4" Neo CD</b>				
NSD1480N	8/16	1,4" exit HF Neo Driver - 160W program power - 110dB@1W/1mt - Treated Titanium diaphragm	490,00	0422T8N610
ND1480	8/16	1,4" exit HF Neo Driver - 160W program power - 110dB@1W/1mt - Titanium diaphragm	410,00	042108N210
ND1460	8/16	1,4" exit HF Neo Driver - 160W program power - 109dB@1W/1mt - Titanium diaphragm	320,00	042108N200
ND1460A	8/16	1,4" exit HF Neo Driver - 150W program power - 110dB@1W/1mt - Aluminum dome	310,00	0422A8M600
ND1424BT	8/16	1,4" exit HF Neo Driver - 140W program power - 109dB@1W/1mt - Titanium diaphragm	240,00	0422T8M900
<b>1" Neo CD</b>				
NSD1095N	8	1" exit HF Neo Driver - 100W program power - 110dB@1W/1mt - Treated Titanium diaphragm	210,00	0421T8N410
ND1090	8/16	1" exit HF Neo Driver - 100W program power - 110dB@1W/1mt - Titanium - PEN	180,00	0421T8N400
ND1070	8/16	1" exit HF Neo Driver - 100W program power - 109dB@1W/1mt - Titanium - PEN	150,00	0421T8M400
ND1018BT	8	1" exit HF Neo Driver - 100W program power - 109dB@1W/1mt - Titanium - PEN	132,00	0421T8M430
ND1050	8/16	1" exit HF Neo Driver - 90W program power - 109.50dB@1W/1mt - Titanium - PEN	150,00	0421T8N500
ND1030	8	1" exit HF Neo Driver - 60W program power - 107dB@1W/1mt - Titanium dome	82,00	0421T8M800
ND1020	4/8/16	1" exit HF Neo Driver - 60W program power - 107dB@1W/1mt - Polyester diaphragm	82,00	0421P8M800
<b>FERRITE COMPRESSION DRIVERS</b>				
<b>1" CD</b>				
HD1050	8	1" exit HF Driver - 100W program power - 107dB@1W/1mt - Titanium dome	102,00	0421081050
HD1040	8/16	1" exit HF Neo Driver - 80W program power - 107dB@1W/1mt - Polyester diaphragm	102,00	0421081040
HD1030	8	1" exit HF Neo Driver - 60W program power - 106dB@1W/1mt - Titanium diaphragm	68,00	0421M8H810
HD125	8/16	1" exit HF Driver - 50W program power - 110dB@1W/1mt - Polyester diaphragm	42,00	0421M8H100
XD125	8/16	1" exit HF Transducer - composed by a HD125 driver assembled on a XT120 horn	58,00	0421M8X100
<b>CONSTANT COVERAGE HORNS</b>				
<b>Horns</b>				
XR2064		Constant Coverage rotatable HF horn - 2" entry - 60° H x 40° V - DI factor 12dB	115,00	0422064000
XR1496		Constant Coverage rotatable HF horn - 1,4" entry - 90° H x 60° V - DI factor 12dB	98,00	0421496000
XR1464		Constant Coverage rotatable HF horn - 1,4" entry - 60° H x 40° V - DI factor 12dB	85,00	0421464001
XT1464		Constant Coverage HF horn - 1,4" entry - 60° H x 50° V - DI factor 18dB - elliptical shape	45,00	0421464000
XR1064		Constant Coverage rotatable HF horn - 1" entry - 60° H x 40° V - DI factor 12dB	65,00	0421064000
XT1086		Constant Coverage HF horn - 1" entry - 80° H x 60° V - DI factor 15dB - elliptical shape	54,00	0421086000
XT120		Constant Coverage HF horn - 1" entry - 90° H x 60° V - DI factor 15dB - elliptical shape	18,00	042108XT10

