

P-Audio

<p>308 A</p>  <p>Speakerkast Actief full-range 3" 8x</p> <p>€ 475</p>	<p>BM-15CXHB</p>  <p>COAXIAL TRANSDUCER Size (in.) 15.0 Power RMS (Watts) 300 Fs (Hz) 50.0 Xmax (mm) 2.5 Sensitivity 1w/1m (dB) 100 Qts 0.23 Vas (lt) 135.08</p> <p>€ 194</p>	<p>BM-D750/8</p>  <p>Paudio driver 2" 100 watt 8 ohm</p> <p>€ 107</p>
<p>308 P</p>  <p>Speakerkast full-range 3" 8x</p> <p>€ 375</p>	<p>BM-8CXa</p>  <p>COAXIAL TRANSDUCER Size (in.) 8.0 Power RMS (Watts) 200 Fs (Hz) 62.0 Xmax (mm) 3.0 Sensitivity 1w/1m (dB) 95 Qts 0.24 Vas (lt) 19.0</p> <p>€ 111</p>	<p>Co-A250F</p>  <p>Paudio crossover 2-weg 3Khz 12"</p> <p>€ 36</p>
<p>450FS</p>  <p>Speaker voor bose cabinet</p> <p>€ 28</p>	<p>BM-D440</p>  <p>HF COMPRESSION DRIVER Size (in.) 1.0 Power RMS (Watts) 60 Fs (Hz) 750.0 Sensitivity 1w/1m (dB) 106 Frequency Range (Hz) 1500-18000 Magnet Material Ferrite</p> <p>€ 58</p>	<p>Co-A300F</p>  <p>Paudio crossover 2-weg 2.5 KHz 15"</p> <p>€ 41</p>
<p>BM-10CXa</p>  <p>COAXIAL TRANSDUCERS Size (in.) 10.0 Power RMS (Watts) 300 Fs (Hz) 42.0 Xmax (mm) 3.0 Sensitivity 1w/1m (dB) 96 Qts 0.26 Vas (lt) 84.12</p> <p>€ 152</p>	<p>BM-D440S</p>  <p>HF COMPRESSION DRIVER Size (in.) 1.0 Power RMS (Watts) 60 Fs (Hz) 750.0 Sensitivity 1w/1m (dB) 106 Frequency Range (Hz) 1500-18000 Magnet Material Ferrite</p> <p>€ 50</p>	<p>CPW-4</p>  <p>PASSIVE 2-WAY CEILING SPEAKER SYSTEM Size (in.) 4.0 Colour White Standard Impedance (Ohm) 16 Ohm Power RMS (Watts) 40 Power Program (Watts) 80</p> <p>€ 52</p>
<p>BM-12CX38</p>  <p>COAXIAL TRANSDUCER Size (in.) 12.0 Power RMS (Watts) 600 Fs (Hz) 48.0 Xmax (mm) 4.5 Sensitivity 1w/1m (dB) 98 Qts 0.23 Vas (lt) 72.94</p> <p>€ 215</p>	<p>BM-D450</p>  <p>Throat Diameter 25 mm (1 in) Mounting Type Bolt-On Nominal Impedance 8 mm D.C Resistance 6.4 ohm Power Capacity 80 W Continuous Program Sensitivity 1W/1M 108 dB</p> <p>€ 60</p>	<p>CPW-6</p>  <p>PASSIVE 2-WAY CEILING SPEAKER SYSTEM Size (in.) 6.0 Colour White Standard Impedance (Ohm) 16 Ohm Power RMS (Watts) 80 Power Program (Watts) 160</p> <p>€ 55</p>
<p>BM-12CXHC</p>  <p>COAXIAL TRANSDUCER Size (in.) 12.0 Power RMS (Watts) 200 Fs (Hz) 53.0 Xmax (mm) 5.0 Sensitivity 1w/1m (dB) 98 Qts 0.3 Vas (lt) 39.0</p> <p>€ 205</p>	<p>BM-D740</p>  <p>HF COMPRESSION DRIVER Size (in.) 1.4 Power RMS (Watts) 75 Fs (Hz) 595.0 Sensitivity 1w/1m (dB) 109 Frequency Range (Hz) 500-18000 Magnet Material Ferrite</p> <p>€ 112</p>	<p>CPW-8</p>  <p>PASSIVE 2-WAY CEILING SPEAKER SYSTEM Size (in.) 8.0 Colour White Standard Impedance (Ohm) 16 Ohm Power RMS (Watts) 80 Power Program (Watts) 160</p> <p>€ 115</p>
<p>BM-15CX38</p>  <p>COAXIAL TRANSDUCER Size (in.) 15.0 Power RMS (Watts) 700 Fs (Hz) 39.0 Xmax (mm) 4.5 Sensitivity 1w/1m (dB) 94 Qts 0.3 Vas (lt) 97.92</p> <p>€ 240</p>	<p>Bm-D750/16</p>  <p>HF COMPRESSION DRIVER Size (in.) 2.0 Power RMS (Watts) 100 Fs (Hz) 595.0 Sensitivity 1w/1m (dB) 108 Frequency Range (Hz) 500-18000 Magnet Material Ferrite</p> <p>€ 107</p>	<p>CS-6FT</p>  <p>CEILING SPEAKER WITH TRANSFORMER (307-70206) Size (in.) 6.0 Power RMS (Watts) 15 Sensitivity 1w/1m (dB) 86 Frequency Range (Hz) 80-18000 Magnet Material Ferrite</p> <p>€ 21</p>

P-Audio

<p>CS-8T</p> <p>CEILING SPEAKER WITH TRANSFORMER (307-70208) Size (in.) 8.0 Power RMS (Watts) 20 Sensitivity 1w/1m (dB) 88 Frequency Range (Hz) 70-18000 Magnet Material Ferrite</p> <p>€ 21</p>	<p>HP-12T</p> <p>HIGH POWER BASS & FULL RANGE Size (in.) 12.0 Power RMS (Watts) 100 Fs (Hz) 62.0 Xmax (mm) 1.0 Sensitivity 1w/1m (dB) 96 Qts 0.66</p> <p>€ 35</p>	<p>P-120-130 LF</p> <p>Nominal Diameter 305 mm / 12 Inch Rated Impedance 8 ohm Power Handling Capacity 600 Watts Sensitivity 2.83 V, 1M 97 dB Effective Piston Diameter 260 mm / 10.2 Inch</p> <p>€ 177</p>
<p>DE34S</p> <p>COMPRESSION DRIVER Size (in.) 1.0 Power RMS (Watts) 40 Fs (Hz) 750.0 Sensitivity 1w/1m (dB) 104 Frequency Range (Hz) 2000-20000 Magnet Material Neodymium</p> <p>€ 60</p>	<p>HP-12W</p> <p>HIGH POWER BASS Size (in.) 12.0 Power RMS (Watts) 100 Fs (Hz) 48.0 Xmax (mm) 2.0 Sensitivity 1w/1m (dB) 97 Qts 0.57 Vas (lt) 99.77</p> <p>€ 35</p>	<p>P-12N</p> <p>Nominal Diameter 305 mm / 12 Inch Rated Impedance 8 ohm Power Handling Capacity 400 W (rms) Sensitivity 2.83 V, 1M 96.6 dB Effective Piston Diameter 265 mm / 10.4 Inch</p> <p>€ 230</p>
<p>DM-720N</p> <p>WOOFER Size (in.) 6 " 6" Power RMS (Watts) 150 Fs (Hz) 112.0 Xmax (mm) 2.5 Sensitivity 1w/1m (dB) 95 Qts 0.32 Vas (lt) 5.79 Frequency Range (Hz)</p> <p>€ 104</p>	<p>HP-15W</p> <p>HIGH POWER BASS Size (in.) 15.0 Power RMS (Watts) 200 Fs (Hz) 34.0 Xmax (mm) 3.0 Sensitivity 1w/1m (dB) 96 Qts 0.49 Vas (lt) 254.26</p> <p>€ 40</p>	<p>P-15N</p> <p>Nominal Diameter 380 mm / 15 Inch Rated Impedance 8 ohm Power Handling Capacity 600 W(rms) Sensitivity 2.83 V, 1M 97.4 dB Effective Piston Diameter 335 mm / 13.2 Inch</p> <p>€ 265</p>
<p>G1250</p> <p>GUITAR LOUDSPEAKER Size (in.) 12.0 Power RMS (Watts) 100 Fs (Hz) 42.0 Xmax (mm) 2.5 Sensitivity 1w/1m (dB) 98 Qts 0.33 Vas (lt) 97.62</p> <p>€ 41</p>	<p>HP-18W</p> <p>HIGH POWER BASS Size (in.) 18.0 Power RMS (Watts) 350 Fs (Hz) 30.0 Xmax (mm) 2.0 Sensitivity 1w/1m (dB) 98 Qts 0.32 Vas (lt) 319.63</p> <p>€ 100</p>	<p>P-18N</p> <p>Nominal Diameter 460 mm / 18 Inch Rated Impedance 8 ohm Power Handling Capacity 800 W(rms) Sensitivity 2.83 V, 1M 98.3 dB Effective Piston Diameter 397 mm / 15.6 Inch</p> <p>€ 310</p>
<p>HP-10</p> <p>HIGH POWER MID-BASS Size (in.) 10.0 Power RMS (Watts) 100 Fs (Hz) 48.0 Xmax (mm) 3.0 Sensitivity 1w/1m (dB) 96 Qts 0.4 Vas (lt) 55.35</p> <p>€ 35</p>	<p>KM-25/black</p> <p>Aluminum Cast Cabinet Imedance 4 ~ 8 Ohm Power Handling 20 W/RMS Frequency Response 150 Hz ~ 20 KHz Sensitivity (2.83V@1M) 87 dB</p> <p>€ 70</p>	<p>PA-208BK</p> <p>Speaker 4.5"</p> <p>€ 0</p>
<p>HP-10T</p> <p>HIGH POWER MID-BASS Size (in.) 10.0 Power RMS (Watts) 100 Fs (Hz) 48.0 Xmax (mm) 3.0 Sensitivity 1w/1m (dB) 96 Qts 0.4 Vas (lt) 55.35</p> <p>€ 35</p>	<p>KM-25/White</p> <p>Aluminum Cast Cabinet Imedance 4 ~ 8 Ohm Power Handling 20 W/RMS Frequency Response 150 Hz ~ 20 KHz Sensitivity (2.83V@1M) 87 dB</p> <p>€ 70</p>	<p>PA-D110</p> <p>COMPRESSION DRIVER Size (in.) 0.87 Throat Diameter (in.) 0.8 Standard Impedance (Ohm) 8 Ohm Power RMS (Watts) 75 Power Program (Watts) 150 Sensitivity 1w/1m (dB) 109</p> <p>€ 34</p>
<p>HP-10W</p> <p>HIGH POWER MID-BASS Size (in.) 10.0 Power RMS (Watts) 100 Fs (Hz) 48.0 Xmax (mm) 3.0 Sensitivity 1w/1m (dB) 96 Qts 0.4 Vas (lt) 55.35</p> <p>€ 35</p>	<p>KM-60</p> <p>SPEAKER SYSTEM Size (in.) 3.0 Material ALUMINIUM Standard Impedance (Ohm) 8 Ohm</p> <p>€ 70</p>	<p>PA-D25</p> <p>COMPRESSION DRIVER Size (in.) 1.0 Throat Diameter (in.) 1.0 Colour Black Standard Impedance (Ohm) 8 Ohm Power RMS (Watts) 30 Power Program (Watts) 60</p> <p>€ 24</p>

P-Audio

<p>PA-D26S</p>  <p>COMPRESSION DRIVER Size (in.) 0.87 Throat Diameter (in.) 0.87 Colour Black Standard Impedance (Ohm) 8 Ohm Power RMS (Watts) 30 Power Program (Watts) 60</p> <p>€ 15</p>	<p>PC-50</p>  <p>Adaptor hoorn- schroef</p> <p>€ 12</p>	<p>PH-1919</p>  <p>NOMINAL COVERAG 100 X 50 CUT OFF FREQUENCY (Hz) 500 THROAT DIAMETER MM 25 MM (1") MOUNTING TYPE BOLT ON</p> <p>€ 15</p>
<p>PA-D38</p>  <p>COMPRESSION DRIVER Size (in.) 0.87 Throat Diameter (in.) 0.87 Colour Black Standard Impedance (Ohm) 8 Ohm Power RMS (Watts) 50 Power Program (Watts) 100</p> <p>€ 40</p>	<p>PC-5025</p>  <p>Adaptor 1 inch - 2 inch</p> <p>€ 15</p>	<p>PH-220</p>  <p>Hoorn 1 inch NOMINAL COVERAGE ANGLE (H x V)-6dB 90° x 75° CUT OFF FREQUENCY (Hz) 800</p> <p>€ 20</p>
<p>PA-DE34S</p>  <p>COMPRESSION DRIVER Size (in.) 1.0 Throat Diameter (in.) 1.0 Colour Black Standard Impedance (Ohm) 8 Ohm Power RMS (Watts) 20 Power Program (Watts) 30</p> <p>€ 39</p>	<p>PC-5038</p>  <p>Adaptor 1,5 inch - 2 inch</p> <p>€ 10</p>	<p>PH-230</p>  <p>Hoorn 1 inch 90 x 90</p> <p>€ 40</p>
<p>PC-20</p>  <p>Adaptor converts drivers ->screw fitting</p> <p>€ 4</p>	<p>PC-90</p>  <p>Adaptor 2x 1,5 inch driver-2 inch hoorn</p> <p>€ 40</p>	<p>PH-2370</p>  <p>Hoorn 1 inch 90 x 40</p> <p>€ 42</p>
<p>PC-25</p>  <p>Adaptor hoorn - schroef</p> <p>€ 4</p>	<p>PH-14525</p>  <p>MATERIAL ALUMINUM THROAT DIOMETER 1 INCH DIMENSIONS DIMENSIONS ARE IN MILLIMETERS MOUNTING TYPE BOLT-ON</p> <p>€ 100</p>	<p>PH-2380</p>  <p>Hoorn 2 inch 90 x 40</p> <p>€ 50</p>
<p>PC-35</p>  <p>Adaptor converts drivers ->screw fitting</p> <p>€ 3</p>	<p>PH-170</p>  <p>Hoorn 90x65 1inch Polymer Glass fiber</p> <p>€ 13</p>	<p>PH-240</p>  <p>Hoorn 1 inch 90 x 55</p> <p>€ 12</p>
<p>PC-3825</p>  <p>Adaptor 1 " naar 1.5 " hoorn</p> <p>€ 10</p>	<p>PH-180</p>  <p>Hoorn 100 X 50 screw-on</p> <p>€ 15</p>	<p>PH-2420</p>  <p>Hoorn Plastic</p> <p>€ 17</p>

P-Audio

<p>PH-2525</p>  <p>Hoorn kunststof</p> <p>€ 16</p>	<p>Ph-4230</p>  <p>Hoorn 2 inch</p> <p>€ 60</p>	<p>PHT-404</p>  <p>Tweeter + hoorn 40w 1 inch 100 x 80</p> <p>€ 23</p>
<p>PH-2723</p>  <p>Hoorn 2" 60 x 40</p> <p>€ 46</p>	<p>PH-4427</p>  <p>Hoorn 2 inch 120 x 60</p> <p>€ 55</p>	<p>PHT-405</p>  <p>Driver + hoorn 20w 1 inch 90 x 90</p> <p>€ 15</p>
<p>PH-3016</p>  <p>Hoorn Kunststof</p> <p>€ 16</p>	<p>Ph-4528</p>  <p>Hoorn 2 inch 60 x 40</p> <p>€ 50</p>	<p>PHT-407N</p>  <p>Tweeter 1 inch Neo 15w 100db</p> <p>€ 26</p>
<p>Ph-316</p>  <p>Paudio hoorn 100 x 100</p> <p>€ 53</p>	<p>PH-4530</p>  <p>Hoorn 2 inch 60 x 40</p> <p>€ 55</p>	<p>PHT-407T</p>  <p>Tweeter 15w 1 inch</p> <p>€ 26</p>
<p>Ph-3220</p>  <p>Hoorn 1 inch 100 x 60</p> <p>€ 55</p>	<p>PH220</p>  <p>Hoorn</p> <p>€ 30</p>	<p>PHT-408</p>  <p>Driver + hoorn 30w 1 inch 90 x 40</p> <p>€ 20</p>
<p>PH-3223</p>  <p>Hoorn 2 inch 90 x 55</p> <p>€ 54</p>	<p>PH240</p>  <p>Hoorn</p> <p>€ 14</p>	<p>PHT-409N</p>  <p>Tweeter Neo</p> <p>€ 26</p>
<p>PH-3520</p>  <p>Hoorn Kunststof</p> <p>€ 25</p>	<p>PH4525</p>  <p>Description HORN Throat Diameter (in.) 2.0 Crossover Frequency (Hz) 400.0 Nominal Coverage Angle (°) 90°x40° Horn Material ABS+Glass fiber Mount Type Bolt-On</p> <p>€ 50</p>	<p>PHT-410</p>  <p>Driver high freq. with Horn 100 x 40</p> <p>€ 28</p>

Alle vermelde prijzen zijn exclusief BTW, tussentijdse prijswijzigingen en drukfouten voorbehouden.

P-Audio

<p>PHT-413</p>  <p>Driver + hoorn 30w 1 inch 90 x 40</p> <p>€ 15</p>	<p>PST555</p>  <p>Tweeter 40w 8 ohm 1.47 inch 40 x 40</p> <p>€ 48</p>	<p>SD-750N</p>  <p>Size (in) 2 " Rated Impedance 8 ohm Power Handling Capacity 125 W (rms) Sensitivity 1W@1m 111 dB Operating Bandwidth 600 Hz - 20K Hz Throat Diameter 51.00 mm /</p> <p>€ 203</p>
<p>PHT-415</p>  <p>Driver + Hoorn 30w 1 inch 100 x 80</p> <p>€ 36</p>	<p>R10/64W</p>  <p>Speaker 64W Blue</p> <p>€ 75</p>	<p>SD-D34S</p>  <p>Driver 8 Ohm</p> <p>€ 53</p>
<p>PHT-416</p>  <p>Size 120 x 200 mm / 4.7 x 7.8 Inch DC Resistance 8.7 ohm Nominal Impedance 8 ohm Resonance Frequency 1576 Hz Power Handling Capacity 40 Watts</p> <p>€ 16</p>	<p>SD-12</p>  <p>Speaker 12 inch 500w 8 ohm</p> <p>€ 223</p>	<p>SN-10C</p>  <p>Speaker 10" 8 ohm</p> <p>€ 135</p>
<p>PHT408T</p>  <p>Driver incl. hoorn 1 inch 20w 8 ohm 90x40</p> <p>€ 35</p>	<p>SD-15</p>  <p>Nominal O.D 15 in / 380 mm Nominal Impedance 8 O Operating Bandwidth 40 Hz - 2.2k Hz \pm 5% Power Handling (IEC) 600 (R.M.S.) Sensitivity @ 1m, 2.83V 97 dB</p> <p>€ 255</p>	<p>SN-10MB</p>  <p>MID BASS WOOFER Size (in.) 10.0 Power RMS (Watts) 200 Fs (Hz) 62.0 Xmax (mm) 3.5 Sensitivity 1w/1m (dB) 96 Qts 0.33 Vas (lt) 36.33</p> <p>€ 83</p>
<p>PST-545</p>  <p>Tweeter 75w 1.75 inch 60 x 40</p> <p>€ 58</p>	<p>SD-18</p>  <p>Nominal O.D 18 in / 460 mm Nominal Impedance 8 O Operating Bandwidth 30 Hz - 1.5k Hz \pm 5% Power Handling (IEC) 800 (R.M.S.) Sensitivity @ 1m, 2.83V 98 dB Transducer Mass 15.32 kg</p> <p>€ 333</p>	<p>SN-12B</p>  <p>WOOFER Size (in.) 12.0 Power RMS (Watts) 300 Fs (Hz) 50.0 Xmax (mm) 3.5 Sensitivity 1w/1m (dB) 100 Qts 0.16 Vas (lt) 82.27</p> <p>€ 103</p>
<p>PST-995</p>  <p>SUPER TWEETER Standard Impedance (Ohm) 8 Ohm Power RMS (Watts) 40 Power Program (Watts) 80 Sensitivity 1w/1m (dB) 103 Frequency Range (Hz) 3500-18000</p> <p>€ 19</p>	<p>SD-450N</p>  <p>Size(in) 1.0" 1.75 VC Rated Impedance 8 ohm Power Handling Capacity 80 W(rms) Sensitivity 1W@1m 106.0 dB Operating Bandwidth 600 Hz - 20K Hz Throat Diameter 24.50 mm /</p> <p>€ 124</p>	<p>SN-12C</p>  <p>COAXIAL NEO WOOFER Size (in.) 305.0 Power RMS (Watts) 250 Fs (Hz) 53.0 Xmax (mm) 2.7 Sensitivity 1w/1m (dB) 96 Qts 0.36 Vas (lt) 67.79</p> <p>€ 177</p>
<p>PST-999</p>  <p>SUPER TWEETER Standard Impedance (Ohm) 8 Ohm Power RMS (Watts) 40 Power Program (Watts) 80 Sensitivity 1w/1m (dB) 106 Frequency Range (Hz) 3500-18000</p> <p>€ 19</p>	<p>SD-740N</p>  <p>Size(in) 1.5 " Rated Impedance 8 ohm Power Handling Capacity 125 W(rms) Sensitivity 1W@1m 111 dB Operating Bandwidth 600 Hz - 20K Hz Throat Diameter 38.00 mm /</p> <p>€ 239</p>	<p>SN-12MB</p>  <p>MID BASS WOOFER Size (in.) 12.0 Power RMS (Watts) 200 Fs (Hz) 50.0 Xmax (mm) 3.5 Sensitivity 1w/1m (dB) 98 Qts 0.29 Vas (lt) 95.33</p> <p>€ 115</p>

P-Audio

<p>SN-15B</p>  <p>WOOFER Size (in.) 15.0 Power RMS (Watts) 400 Fs (Hz) 41.0 Xmax (mm) 3.5 Sensitivity 1w/1m (dB) 99 Qts 0.23 Vas (lt) 196.55</p> <p>€ 126</p>	<p>TM-6</p>  <p>WOOFER Size (in.) 6.0 Power RMS (Watts) 100 Fs (Hz) 58.0 Xmax (mm) 6.0 Sensitivity 1w/1m (dB) 86 Qts 0.36 Vas (lt) 6.6</p> <p>€ 70</p>	<p>X-100FW</p>  <p>Frequency Response (-3dB - 10dB) 60 Hz - 18 kHz Power Handling (Long - term / Short - term) 100 Watts - 250 Watts Sensitivity (1W/1M) 91 dB SPL in Anechoic Chamber Impedance 8 Ohm</p> <p>€ 100</p>
<p>SN-15C</p>  <p>COAXIAL NEO WOOFER Size (in.) 380.0 Power RMS (Watts) 300 Fs (Hz) 45.0 Xmax (mm) 3.25 Sensitivity 1w/1m (dB) 99 Qts 0.32 Vas (lt) 164.12</p> <p>€ 185</p>	<p>TM-8</p>  <p>WOOFER Size (in.) 8.0 Power RMS (Watts) 250 Fs (Hz) 47.0 Xmax (mm) 8.0 Sensitivity 1w/1m (dB) 85 Qts 0.48 Vas (lt) 8.6</p> <p>€ 137</p>	<p>X-100FW-A</p>  <p>Powered 160 W Rms. Crossover Frequency 2 kHz Sensitivity @1W 1M 93 .4 dB Frequency Response 60Hz - 18kHz Nominal Dispersion 90°H X 90°V Maximum SPL 107.5 dB</p> <p>€ 210</p>
<p>SN-15MB</p>  <p>MID BASS WOOFER Size (in.) 15.0 Power RMS (Watts) 300 Fs (Hz) 47.0 Xmax (mm) 3.5 Sensitivity 1w/1m (dB) 100 Qts 0.26 Vas (lt) 176.75</p> <p>€ 127</p>	<p>WN-15S</p>  <p>Nominal Diameter 380 mm / 15 Inch Rated Impedance 8 ohm Power Handling Capacity 300 Watts(rms) Sensitivity 2.83 V, 1M 100.2 dB Effective Piston Diameter 340</p> <p>€ 100</p>	<p>X-12HP</p>  <p>Frequency Response (-3dB - 10dB) 70 Hz - 18 kHz Power Handling (Long-Term / Short-Term) 300 Watts - 900 Watts Sensitivity (1W/1M) 98 dB SPL in Anechoic Chamber Impedance 8 Ohm</p> <p>€ 385</p>
<p>SN-8MB</p>  <p>MID BASS WOOFER Size (in.) 8.0 Power RMS (Watts) 150 Fs (Hz) 70.0 Xmax (mm) 3.5 Sensitivity 1w/1m (dB) 95 Qts 0.3 Vas (lt) 24.01</p> <p>€ 61</p>	<p>WN-18S</p>  <p>Nominal Diameter 380 mm / 15 Inch Rated Impedance 8 ohm Power Handling Capacity 300 Watts(rms) Sensitivity 2.83 V, 1M 100.2 dB Effective Piston Diameter 340</p> <p>€ 100</p>	<p>X-12P</p>  <p>Frequency Response (-3dB - 10dB) 60 Hz - 18 kHz Power Handling (Long-Term / Short-Term) 200 Watts - 600 Watts Sensitivity (1W/1M) 97 dB SPL in Anechoic Chamber Impedance 8 Ohm</p> <p>€ 230</p>
<p>SN-D34S</p>  <p>COMPRESSION DRIVER Size (in.) 1.0 Power RMS (Watts) 40 Fs (Hz) 750.0 Sensitivity 1w/1m (dB) 104 Frequency Range (Hz) 2000-20000 Magnet Material Neodymium</p> <p>€ 62</p>	<p>WN-D34</p>  <p>Size 100 x 58 (mm) / 4" x 2.2" Rated Impedance 8 ohm Power Handling Capacity 40 Watts Above / 2.2kHz 80 Watts Above / 4 kHz Sensitivity 1W@1m 106.0 dB Operating Bandwidth 2kHz -</p> <p>€ 58</p>	<p>X-50FW</p>  <p>Frequency Response (-3dB - 10dB) 70 Hz - 18 kHz Power Handling (Long - term / Short - term) 80 Watts - 200 Watts Sensitivity (1W/1M) 87 dB SPL in Anechoic Chamber Impedance 8 Ohm / 4;8;16</p> <p>€ 70</p>
<p>TM-10</p>  <p>SUBWOOFER Size (in.) 10.0 Power RMS (Watts) 400 Fs (Hz) 55.0 Xmax (mm) 10.0 Sensitivity 1w/1m (dB) 89 Qts 0.57 Vas (lt) 9.94</p> <p>€ 317</p>	<p>WN-D44</p>  <p>Size 100 x 58 (mm) / 4" x 2.2" Rated Impedance 8 ohm Power Handling Capacity 40 Watts Above / 2.2kHz 80 Watts Above / 4 kHz Sensitivity 1W@1m 106.0 dB Operating Bandwidth 2kHz -</p> <p>€ 66</p>	
<p>TM-12</p>  <p>SUBWOOFER Size (in.) 12.0 Power RMS (Watts) 400 Fs (Hz) 49.0 Xmax (mm) 10.0 Sensitivity 1w/1m (dB) 91 Qts 0.52 Vas (lt) 17.51</p> <p>€ 362</p>	<p>WN-D72</p>  <p>Size 150 x 80 (mm) / 6.0" x 3.1" Rated Impedance 8 ohm Power Handling Capacity 100 Watts Above / 1.5 kHz 200 Watts Above 2.5 kHz Sensitivity 1W@1m 110 dB Operating Bandwidth 1.5 kHz</p> <p>€ 138</p>	